




TY-MAX

POLYURETHANE SCREEN MEDIA



TY-MAX POLYURETHANE SCREEN MEDIA

TY-MAX

Ty-Max offers the wear life of a polyurethane panel in a hooked section, so no deck conversion is required.

- Lasts 7-9 times longer than woven wire cloth
- Hooked section installs like woven wire cloth; no deck conversion or additional hardware is required
- Poured using open cast technology, Ty-Max permanently hardens when cured to resist wear and tear
- Tapered openings reduce pegging
- Rugged enough to handle heavy loads in wet or dry applications
- Decreases noise
- Available in side- or end-tensioned hooks

TOP SIZE

Up to 12" depending on the application and tonnage

CUT SIZE RANGE

Square and slotted openings available

Square:

Smallest Square: 3/32"

Largest Square: 4"


Slot:

Smallest Slot: 0.5 X 12 mm

Largest Slot: 3/8" X 1"

BLENDING SCREEN MEDIA

Blending screen media on a single deck helps increase production and extend periods between screen change-outs. Here we've blended two panels of Ty-Max polyurethane on the feed end, with Ty-Wire hybrid screen media on the remaining sections to maximize wear life and open area.



CANADA

East: +1 800-325-5993
West: +1 800-661-0362
info@havercanada.com
www.havercanada.com

BRAZIL

Equipment: +55 (19) 3879-9100
Screen Media: +55 (31) 3661-1371
Service: +55 (31) 3661-3508
info@haverbrasil.com.br
www.haverbrasil.com.br

GERMANY

+49 (0) 251 9793-0
info@haverniagara.com
www.haverniagara.com